Republic of the Philippines ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY

La Paz, Iloilo City

CANVASS PAPER

45	1.20 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	13312 3: 13512 1 135 A 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
The state of the s		BIDS AND AWARDS COMMITTEE
And and Bridge	Document Gode	GF-BAQ-02
	Rev. No.	3
Ji.	Effective Date:	August 3, 2015

R No:	SVP-2022-10			Date: _		Tana Maria	
K NU.	JV: -2022-10			The second secon		Chieran	
ENTL	EMEN:		والمناوية والمناوية		Favealla	hlain	wourstock
\/a	are bereby invited	to goute your price of the articles listed below for it	immediate c	lelivery	lavalla	Digail	yourstook
efore (3:00 PM. We may p	urchase from you all articles in qoutation subject to	THE EXISTING	, regulat	. 30.	To la for	
case	your price should b	e most advantageous to the GOVERNMENT.			200		
Fc	or inquiries, please o	all at Tel. No. (033) 320-7190 Loc 133.	COR	AZON C	COR	3AL, Ì	Ph.D.
				- 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	airman		
anvaş	sed by	Fried Mar I notor John Potorsos	Bids	s and Av			ittee
	Ms. Ann Covelle U	Faja/ Mr. Lester John Rotersos ame and Signature					
	V		است				130,000.00
)eliver	y period upon recei	ot of orde <u>30</u> Calendar Days Ar	pproved Bud	aer (Lub	A distribution		Jumi Islanda da da
		ITEM		Quantity	Unit	100	Unit Cost
tem No.	Product Category			21:9:3		1	
1	Moisture Analyzer	Moisture Analyzer (P 130,000.00)/ unit		21,2 1 2,111	unit	AU E	134 144 144
,		Specification				1-	
		Capacity: (60g)	40.55				
		Minimum readability: (0.02g, 0.001g, 0.01/0.1% (Selectable)(1	10g))			1	
		Repeatability: (0.15% (2g), 0.05% (5g), 0.02% (10g))	i -		19 / 19 / 19 / 19 / 19 / 19 / 19 / 19 /	16	1 30 11 1 15 5
		Drying Heater: (Straight type halogen heater) Power: (400W)		25 3 5 1 Z			
		Temperature range: (50-200°C (1°C increments))		Li in a second	H: -	1000	
		Setting: (There is a time restriction when exceeding 180°C.					<u></u>
		Display: (LCD with backlight)		<u> </u>	1 1 1 1	+	
		Measurement Modes:	Çi li	A.D. W.J			146
		1. Standard	N = 35	lines reig	48 (4)		Account and and a facility of
		2. (Easy start/Automatic end/Timed end)	21	le lacid A	va jak		- India
		3. Rapid drying	∢ *.				
		4. (Easy start/Automatic end/Timed end)	i.,				30 85 166
		Slow drying (Easy start/Automatic end/Timed end) Step drying	11.2			10.86	
		7. (Easy start/Automatic end/Timed end)	111				Holes a
		Measurement Modes 1. Standard	i.				a a professor in the second
		2. (Easy start/Automatic end/Timed end)			313 22 21 31 32 21		
		3. Rapid drying	1 i s 4 i i	A STATE OF THE STA			and the second of the second o
		4. (Easy start/Automatic end/Timed end)	iš i .				
		5. Slow drying	ė.				
		6. (Easy start/Automatic end/Timed end) Step drying	:		1000		r i si bir ibisi
		7. (Easy start/Automatic end/Timed end	\		1		Company and a
		Timer setting: (1-120 minutes or continuous (max 12 hours)) Interface: (RS-232C (9-pin connector) I/O port; USB port)	<u> </u>				
		Measurement conditions data memory: (10)	is a				
		Data memory: (100)					e remains to the time
		Warranty:		13 14 14			
		X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-	(-X-X-X-X				
		For official use at the on going research act	tivity on				4.4
		Utilization of Banana Peel Canistel and Brown	Rice in the				
		development of composite funded by DOST-	PCIEERD		<u> </u>		
		Requested by (Frisian Cousing)			<u> </u>		· · · · · · · · · · · · · · · · · · ·
	Ma harahu nrancas	to furnish and deliver the above articles according	to the spec	- 1	s quote	d abc	ve:
	vve nereby propose	to lutrish and deliver the above attoles decorating	13 13 Op 30				An exercise the
CON	TRACTOR/ DEALE	₹:					
Addre				Tel N	o: <u> </u>		
	HORIZED REPRES	ENTATIVE:		- }	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		1. 1
17011	: 1 \(\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	NAME		ignature			Date
			:		أو مرادلات	,,,, (e	