

PURCHASE ORDER

ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY
Burgos St., LaPaz, Iloilo City

DOC # 42955

Supplier :	MOLAVE TRADING INC.	P.O. No. :	2022-02-052
Address :	891 Edsa South Triangle Diliman, Quezon City	Date :	February 14, 2022
TIN :	000-390-460-000	Mode of Procurement :	Small Value Procurement


Gentlemen:
Please furnish this Office the following articles subject to the terms and conditions contained herein:

Place of Delivery :	Burgos Street, La Paz, Iloilo City	Delivery Term :	90-120 Calendar days upon signing of P.O
Date of Delivery :		Payment Term :	CHARGE

Stock/ Property No.	Unit	Description	Quantity	Unit Cost	Amount
1	unit	Centrifuge - Thermo Scientific mySpin 12 Mini Centrigue, Cat#75004081 Technical Specs: Capacity: 12x2mL; Max Speed: 12,500rpm; Max. RCF 9,800 x g; Noise Level 51-53 dB(A) Temperature Range: Ambient temperature; Type: Benchtop Centrifuge Includes: 12 x 1.5/2.0mL rotor, 32 x 0.2mL rotor (singles or 4 x 8 strip), 0.2mL adapter (set of 12), 0.5mL adapters (set of 12), Universal power adapter 110-240V 50/60 Hz with 4 interchangeable plug types Description:mySPIN 12 Mini Centrifuge; Electrical Requirements 110/240 V 50/60 Hz Net weight: 3.11lb(1.14kg); Refrigerated: No; Run Time: 1sec to 30min (1sec increment) Quick Spin; Standards: IEC 61010-1, IEC 61010-2-020 (refer to manual for more detail) Dimensions: (HWD) 4.4 x 6.7 x 8 in. (11.4 x 17.1 x 20.3 cm) Certifications/Compliance CSA, CE, UL Includes complete installation and demonstration Warranty period: 1 year	1	65,000.00	65,000.00
2	unit	Digital Orbital Shaker - Thermo Scientific™ Digital Microplate Shakers Speed Range 150 - 1200 rpm; Speed Control Accuracy ±1% of set speed up to 299rpm ±2% 300 to 1200rpm; Orbit: 2.5 mm; Capacity 1 kg @1200 rpm / 4 kg @ ≤400 rpm (accessory included); Control: LED; Humidity Range 20 - 85% RH; Load Bearing Capacity 1 kg @1200 rpm / 4 kg @ ≤400 rpm; Net Weight:12.8 kg / 28.2 lbs Platform Material Stainless steel; Plug Type 120V US/JP Plug; Shipping Weight:15 kg / 33 lbs; Timer 0 (Continuous), 1min - 99h59min; Timer Range 1min - 99h59min Display: LED; Display Accuracy: 1 rpm; Operating Conditions 5° - 40°C, 20 - 85% RH Certifications/Compliance cCSAus, CE, RoHS; Dimensions (L x W x H) Exterior 487 x 387 x 264mm / 19.2 x 15.2 x 10.4 in; Dimensions (D x W x H) Interior 383 x 260 x 145	1	63,401.40	63,401.40
Page 1 of 2				Sub-Total	128,401.40

(Total Amount in Words): Two Hundred Forty Thousand Five Hundred Ninety Five Pesos and Ninety Centavos

In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of delay shall be imposed on the undelivered item/s.	
Conforms:	Very truly yours,
 EMMANUEL A. ACERO MOLAVE TRADING INC. Name of Supplier February 23, 2022 Date	 RAUL F. MUYONG, Ed.D. University President FEB 18 2022 Date

Fund Cluster :	SMF	ORS/BURS No. :	2022-02-0037
Funds Available :		Date of the ORS/BURS:	
	JESSICA M. GENZOLA Accountant IV	Amount :	240,595.90