然自

Republic of the Philippines ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY

La Paz, Iloilo City

CANVASS PAPER

epartment:	BIDS AND AWARDS COMMITTEE			
ocument Code:	QF-BAC-02			
ev. No.:	3			
ffective Date:	August 3, 2015			

					August 3, 2013	
PR No:	SVP-2022-05	51	Date:			
Yo Please pefore a n case	submit your qoutation 3:00 PM. We may pur price should be	d to qoute your price of the articles listed below for immediate on in sealed envelope to the Supply Officer, or thru the bearer urchase from you all articles in qoutation subject to the existing most advantageous to the GOVERNMENT. Sall at Tel. No. (033) 320-7190 Loc 133.	on g regula	tion gove	· · · · · · · · · · · · · · · · · · ·	
Ms. Ann Loyelle O. Faja/ Mr. Lester John Rotersos Bio				Chairman ds and Awards Committee		
Deliven	y period upon receir	ot of orde 30 Calendar Days Approved Bud	lget: (Php)	135,000.00	
tem No.	Product Category	ПЕМ	Quantity	Unit	Unit Cost	
1	FM Transmitter Package	Low Power FM Transmitter Package: Built-in Power Supply, Transmission Cable, Transmitting Antenna, Audio Cable, Power Cable Specifications: Frequency Range: 87.5-108 MHz Adjustable Power Out: Up to 50W Freq. Setting Step: 10 KHz Audio Input Impedance 600Ω, Balance Separation 60dB Pilot Signal Modulation Audio Input Level: ±10dBm,step 0.01dB S/N: ≥75dB (30H~15kHz,100%) Audio Harmonic Distortion: <0.05% Audio response: ±0.05dB(30Hz~15KHz) Output Load Z:50Ω Output Power:(Adjustable) 50W Pre-mphasis: 0µS,50µS,75µS Deviation: ±75kHzPilot Frequency:19 kHz±1Hz Sub-carrier Suppression: ≥65dB RF Output Connector: SO239 or 7/16'(female) or 7/8' Flange Pilot Signal Mod: 8%~10% Operating Voltage: 220VAC 60 Hz	1	unit		
2	Antenna Analyzer	Antenna Analyzer, standalone (Portable)unit 1.8-500 MHz, Cross Pointer Analog display (SWR&Impedance) LCD Color Screen, Dial Tune Knob, UHF & Type-N Connector,RF Connector Type: UHF female, SO-239, Band Selection Control: Rotary switch Frequency Control Style:Dial Internal Battery Operation Six AA batt External Power Input Voltage: 8-16 Vdc Includes a Type-N connector for use above 300 MHz.	1	Unit		
3	Oscilloscope	Digital Oscilloscope 4 Channels, 100 MHz Bandwidth UltraVision: Deeper memory 12 Mpts upgradable to 24 Mpts 12 Megs of Memory standard) Up to 30,000 wfms/s Waveform capture rate HUGE 7" screen WVGA(800X480) TFT USB HOST, USB DEVICE, LAN, Aux (TrigOut /PassFail) Incredible display with multi-Level intensity grading display Realtime waveform Record, Replay, function	2	Unit		
		x-x-x-x-x-x-x-x-x-x-x-x-x-x-x-x-x-x-x-		,		
		For official use at the Electrical and Electronics Dept.				
		Requested by (Ana Ancheta)				
	RACTOR/ DEALER:	furnish and deliver the above articles according to the specif	Tel No:	quoted a	ibove.	

NAME

Signature

Date