

## Republic of the Philippines ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY

La Paz, Iloilo City
• Trunkline: (033)320-7190 • Telefax: (033)329-4274

• Website; www.isatu.edu.pn



## **Section VII. Technical Specifications**

ITEM NO.	SPECIFICATION			STATEMENT OF COMPLIANCE				
110.	[Bidders must state here either "Comply" or "Not Comply" against each of the individual paramete each Specification stating the corresponding performance parameter of the equipment offers Statements of "Comply" or "Not Comply" must I supported by evidence in a Bidders Bid and crop referenced to that evidence. Evidence shall be form of manufacturer's un-amended sales literate unconditional statements of specification and compliance issued by the manufacturer, sample independent test data etc., as appropriate. A state that is not supported by evidence or is subseque found to be contradicted by the evidence presedender the Bid under evaluation liable for reject statement either in the Bidder's statement of coor the supporting evidence that is found to be founding Bid evaluation, post-qualification or the eduring Bid evaluation, post-qualification or the eduring Bid evaluation post-qualification or the eduring Bid evaluation or supplier liable for prosecution.						ividual parameters of presponding quipment offered. Comply" must be ers Bid and crossdence shall be in the ded sales literature, cification and facturer, samples, oppropriate. A statement e or is subsequently evidence presented will liable for rejection. A statement of compliance is found to be false either fication or the execution is a straudulent and	
		Procurement of Lathe Machine fo	or CE	EA F	und 10	01		
ITEM NO.		Specification			QTY	BRAND	Statement of Compliance	
1	LATHE MACHINE	GAP BED LATHE MACHINE Specifications:		lot	1			
	,	Height of centers, 180mm	-					
		MaximumDistance Between Centers, 1000m	m					
		Max. swing over bed, 350-360mm						
		Max. swing over gap, 500-580mm			-			
		Max. swing over cross, 190-220mm						
		Length of gap in front of faceplate, 160mm				<u> </u>		
		Max. Bar Stock 38-52mm						
		Thread No.15						
		Taper of single hole, morse No.5						
		Diameter of spindle/bore, 40-52mm						
		Taper of center sleeve, morse No.3						
		Max. cross feed, 230mm						
		Standards Accessories:						
		3 jaw chuck, T-wrenchs, 3 jaw & 4 jaw chuchase	ek					
	'	Center sleeve, face plate, steady rest, follow rest						
		lathe dog, tail stock spindle sleeves, changear						
		tool bit holders (left, right and center), knurling tools						
		cut-off tool holder with tool bit, drill chuc, dead						
		center,live center,pipe center and surface gauge	ce					
		Warranty period 1 year						
		Delivery period 20 days			,			