

Republic of the Philippines
ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY

La Paz, Iloilo City

• Trunkline: (033)320-7190 • Telefax: (033)329-4274

• Website: www.isatu.edu.ph




Section VII. Technical Specifications

ITEM NO.	SPECIFICATION	STATEMENT OF COMPLIANCE
	ABC (P 324,500.00)	[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution.]

Procurement of Demolition and other Supplies Fund 164

ITEM NO.	Specification	UNIT	QTY	BRAND	Statement of Compliance
1	Demolition Hammer Demolition Hammer / Breaker (Engine Powered) Specifications: Oil Capacity: 12L, Displacement: 49.3cc, Single Impact Force: 25-55 J, Impact Rate: 770-1500s/min, Speed: 3,000-6,500 rpm, Dry Weight: 17.5 kg, 2-Stroke, 30mm HEX Shank Inclusions: Trolley, Flat Chisel, Pointed Chisel	set	5		
2	Table Saw Table Saw, 1,500W, 10", Continuous power input: 1,500W, Cutting cap. on 90° : 91 mm (3-9/16"), Cutting cap. on 45° : 60 mm (2-1/2"), Bevel cutting cap.: 0° to 45°, Blade diameter: 255 mm (10"), Hole diameter: 25.4 mm (1"), No load speed: 4,500 rpm, Dim: 72.6 cm x 98.4 cm x 33.3 cm (28-1/2" x 38-3/4" x 13-1/8"), Net weight: 38 kg, Power supply cord: 2.5 m (8.26 feet), With wheeled Stand - Stand dimensions: 101.5 cm x 59 cm x 56 cm, Wheeled Stand Net weight: 24 kg.	set	10		
3	Cut-off Machine Cut-off machine, Specification: Powerful 1850w Motor, 355mm Cutting Diameter, For wood, Metal and Stone, Load Speed: 3800, Input Voltage:220v, 50/60Hz	set	4		
4	Planer Power planer, Continous Rating Input: 600W, Power Voltage: 220-240V, No-Load Speed: 16000 r/min, Frequency: 50-60Hz, Planing Width: 82mm (3-1/4), Planing Depth: 1mm High power-to-weight ratio (2.5kg / 5.5lbs) for superior performance, Can be used with both standard planer blades and double-edged mini blades, Simple blade setting system for fast blade installation.	set	5		
5	Circular Saw Mini electric circular saw, Power Source: AC, Saw Type: Mini Saw, Weight: 2260g, Rated Voltage: 220V, Wattage: 300-499W, Usage: Commercial Manufacture, No-Load, Speed: 3400rpm, Application: Wood Saw, Dimensions: 270 x 93 x 60 mm/10.63" x 3.66" x 2.36", Rated Input Power: 400W, Frequency: 50Hz/60Hz,	Set	5		
6	F Clamp Heavy Duty F-Clamp, Application: Woodworking, Specifications: 5 * 10cm (0.3kg)/5 * 20cm (0.38kg)/5 * 30cm (0.43kg), Non-slip handle,	unit	10		
7	Bench Grinder/Polishing Machine Bench Grinder Polishing Machine, Twin Grindstone,220-240V, 370W, 3000r/min for Multiple Purposes, Grinding Disc	unit	1		



Republic of the Philippines
ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY
 La Paz, Iloilo City

• Trunkline: (033)320-7190 • Telefax: (033)329-4274
 • Website: www.isatu.edu.ph



		Size:150*20*32mm/5.9*0.8*1.3in, Safety Linear Speed: 35m/s, Rated Rotation Speed: 3000r/min, Rotor:Copper Core				
8	Drill Bit	Square hole saw tenon chisel (for Mortising Drilling Carving) , Material: #45 steel, 4pcs per set Square hole sizes: 1.) 6.4 2.) 8 3.) 9.5 4.) 12.7mm	set	5		
9	C Clamp	Heavy Duty clamp, Cast Iron, 3pc per set, Sizes: 1 1/2 x 1 1/2, 2 1/2 x 2 1/2, 3 1/2 x 3 1/2 Clamping Force: 650-1000 lb.	set	10		
10	Saw	Miter Saw, Cutting capacity, 0° 89 x 320 mm, 0° with spacer (max. vertical) 100 x 250 mm, 0° with spacer (max. horizontal) 60 x 350 mm, 45° mitre 89 x 226 mm, 45° incline 50 x 320 mm, Mitre setting 52 ° L / 60 ° R, Bevel setting 47 ° L / 47 ° R, Tool dimensions (w×l×h) 820 x 560 x 490 mm, No-load speed 3,700 – 5,000 rpm, Saw blade dia. 254 mm, Saw blade bore dia. 30 mm, 24.2 kg, 220-240V, Rated Power: 1,800-2,000 W, with LED/laser guide	unit	2		
11	pliers	Adjustable Plumbing pliers, Length: 250mm, Heavy Duty, Pipe capacity Diameter: 2 inches, Nut Capacity Diameter: 46mm	pcs	10		
12	Vise	Bench Swivel Vise with anvil, Jaw Width: 8" x Jaw Opening: 5" x Throat Depth: 3.25"	set	5		
13	Drill press	220-240V, 250 Watts, 13mm Maximum Bit capacity, Spindle Travel: 50mm, Table Size: 160 x 160mm, Base Size: 290 x 290mm, Column Diameter: 46mm, Height -580mm	set	1		
14	Welding and Cutting Outfit	Oxygen Acetylene Welding and Cutting Outfit, (Set: Torch Handle, Oxygen Attachment, Oxygen Regulator, Acetylene Regulator, Welding Nozzles (Nos. 3, 5, & 7), Mixer, Cutting Nozzle, Twin Hose: 15ft x 1/4" C/W Fittings, Tip Cleaner, Goggles Spark Lighter), Package Inclusion: Oxygene Tank and Acetylene Tank	set	1		
15	Fusion Machine	Heavy Duty Fusion Machine for PPR, PVC, and PE plastic pipes, Capacity: 20 to 63mm, Dies: 20, 25,32, 40, 50, and 63mm, 800 Watts, 220-240V Inclusion: stand, allen key, screwdriver, screws, and carrying case	set	2		
		Delivery Period 20 calendar days				
		Warranty 1 year				

BIDDER:

Printed Name & Signature of Bidder