

PURCHASE ORDER
ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY
Burgos St., LaPaz, Iloilo City

DOC # 67373

Supplier :	JVS AUDIO SYSTEM	P.O. No. :	2024-11-292
Address :	Door 3 Mayflower Apt., Mabini Street, San Agustin Iloilo City	Date :	November 28, 2024
TIN :	009-667-485-005	Mode of Procurement :	Small Value Procurement

Gentlemen:
Please furnish this Office the following articles subject to the terms and conditions contained herein:


Place of Delivery :	Burgos Street, La Paz, Iloilo City	Delivery Term :	30 Calendar Days upon receipt of P.O
Date of Delivery :		Payment Term :	CHARGE

Stock/ Property No.	Unit	Description	Quantity	Unit Cost	Amount
1	units	SPEAKER - Powered Speaker 10" BRAND: SOUND LOGIC MODEL: SL10A ACTIVE SPEAKER Features: Drivers: 10" Woofer 300 Watts, 1" Titanium Tweeter 50 AC Input: 220-240 vac - 50hz Watts Power: 300 Watts Continuous 600 Watts Peak Maximu SPL: 121d Freq Range: 60hz to 20 kHz Dimension HxWxD: 56cm x 34cm x 28.5cm Input: Balanced XLR	4	21,700.00	86,800.00
2	units	AUDIO MIXER - Mixer 12 channels BRAND: YAMAHA MODEL : MG12XU ANALOG MIXER D-PRE mic preamps deliver clean, transparent, and natural sound 3-band EQ on all mono channels for sound-shaping 1-knob compressors provide straightforward dynamics control Class-compliant USB 2.0 for recording and playback with computers and tablets SPX effect processors provide you with a comprehensive suite of 24 effects Pad switch on mono inputs for managing loud sources Metal chassis for durability	2	28,500.00	57,000.00
3	rolls	CABLE - Microphone Cable BRAND: STRANDTZ Features: Type: Stereo Microphone Wire Cable thickness: approx. 0.7 cm Durable, flexible design eliminates kinks and twits High fidelity transmission Heavy duty Low impedance	1	7,500.00	7,500.00
4	sets	CONNECTOR - Audio Connector Male and Female BRAND: NEUTRIK MODEL: NC3FX NC3MXX XLR Male Features: Capacitane between contacts: ≤ 4 pF Contact resistance: ≤ 3 mΩ Dielectric strength: 1, 5 kVdc Insulation resistance: > 10 GΩ (initial) Rated current per contact: 16 A Rated voltage: < 50 V 3 pole female cable connector with Nickel housing and silver contacts XLR Female Features: Capacitane between contacts: ≤ 4 pF Contact resistance: ≤ 3 mΩ Dielectric strength: 1, 5 kVdc Insulation resistance: > 10 GΩ (initial) Rated current per contact: 16 A Rated voltage: < 50 V 3 pole female cable connector with Nickel housing and silver contacts	10	750.00	7,500.00
Page 1 of 2				SubTotal	158,800.00

(Total Amount in Words): ONE HUNDRED SIXTY TWO THOUSAND SEVEN HUNDRED SIXTY PESOS ONLY

In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of delay shall be imposed on the undelivered item/s.

Conforme:	Very truly yours
	
JVS AUDIO SYSTEM	GABRIEL M. SALISTRE, JR., PEE, DIT
Name of Supplier	University President
	
Date	Date

Fund Cluster :	164	ORS/BURS No. :	2024-12-1929
Funds Available :		Date of the ORS/BURS:	
		Amount :	162,760.00
JESSICA M. GENZOLA			
Accountant IV			

PURCHASE ORDER
ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY
Burgos St., LaPaz, Iloilo City

DOC # 67373

Supplier :	JVS AUDIO SYSTEM	P.O. No. :	2024-11-292
Address :	Door 3 Mayflower Apt., Mabini Street, San Agustin Iloilo City	Date :	November 28, 2024
TIN :	009-667-485-005	Mode of Procurement :	Small Value Procurement

Gentlemen:
Please furnish this Office the following articles subject to the terms and conditions contained herein:

Place of Delivery :	Burgos Street, La Paz, Iloilo City	Delivery Term :	30 Calendar Days upon receipt of P.O
Date of Delivery :		Payment Term :	CHARGE

Stock/ Property No.	Unit	Description	Quantity	Unit Cost	Amount
5	pcs	CONNECTOR - Audio Connector PL Mono BRAND: NEUTRIK MODEL: NP2X PL MONO PLUG Features: 1/4" professional phone plug, 2 pole, nickel contacts, nickel shell The heavy duty professional phone plug series improves on the design of the existing C series by offering the thinnest available A-gauge 1/4" plug with unique Neutrik chuck type strain relief on the market. The slimline shell with a width of 14.5 mm meets the most recent requirements for highest density jackfields (15.88mm jack pitch)	8	270.00	2,160.00
6	pcs	CONNECTOR - Baby Plug BRAND: AMPHENOL MODEL: KS3PC Baby Plug Features: Mono or TRS (Stereo) AX Series Shell design. Cable O.D. 2.5mm to 5mm (0.098" to 0.196") Robust diecast shell in satin nickel or black finish. Nickel or Gold contact plating Precision machined contacts. Flexible grommet cable protection Quick and easy assembly Warranty Period: 1 year free service, Installation: Free After Sales Services: 6 months carry-in service **** Nothing Follows**** For official use of the library clients for upgrading the AVR facilities and equipment 'Requested by: Corazon C. Corbal	6	300.00	1,800.00
Page 2 of 2				GrandTotal	162,760.00

(Total Amount in Words): ONE HUNDRED SIXTY TWO THOUSAND SEVEN HUNDRED SIXTY PESOS ONLY

In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of delay shall be imposed on the undelivered item/s.

Conforme:	Very truly yours,
<div>JVS AUDIO SYSTEM Name of Supplier 12/11/24 Date</div>	<div>GABRIEL M. SALISTRE, JR., PEE, DIT University President DEC 11 2024 Date</div>

Fund Cluster :	164	ORS/BURS No. :	2024-12-1924
Funds Available :		Date of the ORS/BURS:	
JESSICA M. GENZOLA Accountant IV		Amount :	162,760.00