

(PR/JR NO.)

Republic of the Philippines **Bids and Awards** Department: Committee ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY QF-BAC-02 Doc. Code: La Paz, Iloilo City Rev. No.: 00 REQUEST FOR QUOTATION July 1, 2022 Effective Date:

2024 AUG Date SVP-2024-205

68877 Doc Track No.

TO: ALL PROSPECTIVE SUPPLIERS

- 1. The Iloilo Science and Technology University (ISAT U) through the Office of the BIDS and AWARDS COMMITTEE, intends to procure AUTOMATED AUTOCLAVE for CY 2024, in accordance with Section 53.9 (Negotiated Procurement - Small Value Procurement) of the 2016 Revised Implementing Rules and Regulations of Republic Act No. 9184.
- The Approved Budget for the Contract (ABC) is <u>Seven Hundred Ten Thousand Pesos (710,000.00)</u>. The period for the performance of this obligations shall not go beyond the validity of the appropriations for this project. For purposes of evaluation, comparison and ranking of bids/offers, the suppliers who submitted the single / lowest calculated responsive quotation shall be awarded the Purchase Order after evaluation by the Technical Working Group (TWG).
- The Procurement Mechanism to be used is "BY LOT".
- Please quote your best offer for item/s described herein, subject to the <u>(Terms of</u> Conditions/Technical Specifications) of this Request for Quotation (RFQ). Subject your quotation duly signed by your authorized representative not later than 3:00 PM on Procurement Management Office (PMO) – BAC Secretariat Office, ISAT U, Burgos St., La Paz, Iloilo City. Quotations may also be submitted through email at the address and contact numbers indicated below.
- 5. Quotation shall be enclosed in a sealed envelope and addressed the PMO BAC Secretariat at the address given above. The envelope should have the PR/JR Number boldly and conspicuously identified.
- The successful proponent must be able to meet the following requirements:
 - The Terms and Conditions/Technical Specifications, as provided. 6.1
 - The Schedule of Requirements, as provided. 6.2
 - A copy of your 2024 Business Permit/Mayor's Permit and PhilGEPS Registration 6.3 Number is also required to be submitted along with your signed quotation/proposal. (see GPPB Resolution No. 09-2020 Item 6.2)
 - The Omnibus Sworn Statement (GPPB-prescribed forms), Income/Business Tax 6.4 Return for ABC's above Php 500,000.00 will also be required to be submitted prior to award. (see GPPB Resolution No. 09-2020 Item 6.3)
 - The quotation should be valid for sixty (60) calendar days from the due date indicated above.
 - ISAT U reserves the right to request for additional documents that it deems necessary in order to make any decision or any quotation.
 - All prospective suppliers must fill out the RFQ provided by ISAT U. Any quotation other than what is provided by the Procuring Entity (PE) or is patently not complying with the RFQ requirements may not be considered.
 - 10. ISAT U reserves the right to accept or reject any quotation, to annul the procurement process, or not to award the contract without thereby incurring any liability to the affected bidders.
 - 11. Submission of quotation in response to this request shall be construed as commitment to undertake the services in accordance with the terms and conditions or specifications, and schedule of implementation set forth in this RFQ.
 - 12. For any clarification, you may contact us at (033) 320-7190 local no. 133 or email us at bac.isatu@gmail.com

G. CORONA **BAC Chairperson**

bacsec.2024 F101 1.



Republic of the Philippines

ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY

La Paz, Iloilo City

Department:	Bids and Awards Committee
Doc. Code:	QF-BAC-02
Rev. No.:	00
Effective Date:	July 1, 2022

REQUEST FOR QUOTATION

(PR/JR NO.)

SVP-2024-205

Date

AUG n 7 2024

Doc Track No.

68877

INSTRUCTIONS

- 1. Accomplish this RFQ correctly, accurately, and completely.
- 2. Do not alter the contents of this form in any way.
- All technical specifications are mandatory. Failure to comply with any of the mandatory requirements will disqualify your quotation.
- 4. Failure to follow these instructions will disqualify your entire quotation.

TECHNICAL SPECIFICATION

- 1. Please quote your **best offer** for item/s below. Please do not leave any blank items. Indicate "F" if the item offered is for FREE or "NA" for NOT AVAILABLE in the "Total Cost" if applicable.
- 2. Bidders must state <u>"Comply"</u> or any equivalent term in the column "Bidder's Statement of Compliance" against each of the individual parameters of each Specification.

			ABC per			To be filled up by Supplier			
Item No.	Product Category	Description/Specification	Line Item (If applicable)	QTY	Unit	Bidder's Offer (State brand & model)	Bidder's Statement of Compliance	Unit Cost (VAT Inclusive)	Total Cost (VAT Inclusive)
1	Automated Autoclave	Specifications:		1	set				
		Type: Fully Automatic type Chamber Type: Round Vertical type Capacity: 81 liters in size (ØxH)m/m: 400 x 650 Dimension (WxDxH)m/m: 670x620x1110 (about) Heater Capacity: 4kw Temp. Range: Ambient to 130°C Temp. Controller LED Microprocessor programmable control Time range: 99 Hours 59 min Digital Display Temp. Sensor: Pt-100? (Exclusively for sterilizing, Auto tuning) Accuracy: ±0.5°C Material(in): Stainless steel (out): SS41 steel late and powder coating Door system (out): one touch handle type (single screw door) Basket: Stainless steel (#304) manufactured for sterilizing 2ea Pressure range: 0~3kg/cm2 (Analog) Using pressure: 0~1.2kg/cm2 Wheel: Silicon carrior w/ fixed screw frame Electronic power: AC 220v, 60Hz Single-phase Safety device: Safely pressure valve, over temp, controller N.F.B. Buzzer, switch, -etc- 10KVA AVR Automatic Voltage Regulator (AVR) 10KVA Plug and cord 3 years warranty on parts and services							



Republic of the Philippines

ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY

La Paz, Iloilo City

	Bids and Awards
Department:	Committee
Doc. Code:	QF-BAC-02
Rev. No.:	00
Effective Date:	July 1, 2022

REQUEST FOR QUOTATION

(PR/JR NO.) : **SVP-2024-205** Date : AUG 1 7 2024 68877

Body: Aluminum die-casting metal frame, Protective covering Optical System: Infinity optical system Illumination System: Bulli-in transmitted Illumination system; LED Power Consumption 0.5 W (nominal values) Pocusing: Stage height movement (coarse movement stroke: 15 mm), coarse adjustment limit stoper, Torque adjustment for coarse adjustment knob, Fine focus knob (minimum adjustment gradations: 2.5 mm) Revolving Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Travelling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 300 inclined binocular tube interpupillary distance adjustment range: 48 – 75 mm, Eyepoint distance adjustment ange: 48 – 75 mm, Eyepoint distance adjustment ange: 48 – 75 mm (N) x 30.0 mm (N). 23.2 mm Objectives: Plan adromat, antifungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current Act 10x-240 v 50/60 Nt. 0.4 Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N. 20), quadruple revolving nosepiece; right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), Including AC adapter, fixing bett for transportation. (10m Illumersion 10ml Oil Immersion 1	Binocular electric	Specifications:	4	sets			
Protective covering Optical System: Bullt-in transmitted Illumination System: Bullt-in transmitted Illumination System, LED Power Consumption 0.5 W (nominal values) Focusing: Stage height movement (coarse movement stroke: 15 mm), coarse adjustment limit stopper, Torque adjustment for coarse adjustment thoob, Fine focus knob (minimum adjustment gradations: 2.5 jmm) Revolving Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 30o inclined binocular tube interpupillary distance adjustment range: 48 – 75 mm, Eyepoint adjustment: 370.0 – 432.9 mm Objectives: Plan achromat, anti- fungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100xoli NA: 1.25 W.D.: 0.13 mm tyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current Act 100-240 V 51060 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4x, 10x, 40x, 10x), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml (12 morrison 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 with print (10 pc) 1/YCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X	microscope	Body: Aluminum die-casting metal frame.					
System: Infinity optical system Illumination Systems, LED Power Consumption 0.5 W (nominal values) Focusing: Stage height movement (coarse movement stroke: 15 mm), coarse adjustment limit stopper, Torque adjustment for coarse adjustment stroke: 15 mm), coarse adjustment limit stopper, Torque adjustment for coarse adjustment gradations: 2.5 mm) Revolving Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 300 inclined binocular tube interpupillary distance adjustment: 370.0 — 432.9mm Objectives: Plan achromat, anti- fungus 4x Na: 0.10 W.D.; 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100x01 NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (K4, 10X, 40X, 10X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml (21 bottle) Dust Cover Type-015 with print (10 pc) UYCP Power Cord (10 pc) AF53460 Eyepiece pointer (110 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X		,					
System; Built-in transmitted Illumination system, LED Power Consumption 0.5 W (nominal values) Focusing: Stage height movement (coarse movement stroke: 15 mm), coarse adjustment flinit stopper, Torque adjustment for coarse adjustment knob, Fine focus knob (minimum adjustment gradations: 2.5 jum) Revolving Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Traveling range: 75 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 30o inclined binocular tube interpupillary distance adjustment: angle. 48 – 75 mm, Eyepoint adjustment: 370.0 – 432.9mm Objectives: Plan achromat, anti- fungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.55 W.D.: 0.6 mm 100x0il NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (Fis): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/50 Hz: 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (Fi.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 10XX), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml (21 bottle) Dust Cover-1015 Wilty print (20ver-015 (WP) Dust Cover-1015 Wilty print (10 pc) UYCP Power Cord 10 (70 pc) AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
system, LED Power Consumption 0.5 W (nominal values) Focusing: Stage height movement (coarse movement stroke: 15 mm), coarse adjustment limit stopper, Torque adjustment for coarse adjustment knob, Fine focus knob (minimum adjustment gradations: 2.5 jum) Revolving Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 300 inclined binocular tube interpupillary distance adjustment: 370.0 - 432.9mm Objectives: Plan achromat, antifungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 3.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100x0li NA: 1.25 W.D.: 0.13 mm Eyeplece (10x): Fleid Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current & Clo 2-94 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml Oil Unit Oil Immersion 10ml (20 bottle) Dust Cover-015 with print (10 pc) VPC Power Cord (10 pc) AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX							
Focusing: Stage height movement (coarse movement stroke: 15 mm), coarse adjustment limit stoper, Torque adjustment for coarse adjustment gradations: 2.5 m) Revolving Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 300 inclined binocular tube interpupillary distance adjustment range: 48 – 75 mm, Eyepoint adjustment: 370.0 – 432.9 mm Objectives: Plan achromat, antifungus 4 x No: 0.10 W.D.; 27.8 mm 10 x No: 0.25 W.D.: 8.0 mm 40 x No: 0.5 W.D.: 0.6 mm 100xXII NA: 1.25 W.D.: 0.15 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9 kg Rated Voltage/Electric Current AC 100-240 t S)(60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belf for transportation. (10 unit) Oil Immersion 10ml (20 bottle) pust Cover-015 w/bprint Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord (10 pc) AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service **X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
movement stroke: 15 mm), coarse adjustment limit stopper, Torque adjustment for coarse adjustment knob, Fine focus knob (minimum adjustment gradations: 2.5µm) Revolving Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 300 inclinde binocular tube interpupillary distance adjustment range: 48 – 75 mm, Eyepoint adjustments 370.0 – 432.9mm Objectives: Plan achromat, antifungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100x0il NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml (01 bitmersion 10ml Oil Dimmersion 10ml (02 bottle) plust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc.) WCP Dower Cord (10 pc.) AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service							
limit stopper, Torque adjustment for coarse adjustment knob, Fine focus knob (minimum adjustment gradations: 2.5µm) Revolving Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 300 inclined binocular tube interpupillary distance adjustment: 370.0 – 432.9mm Objectives: Plan achromat, anti- fungus 4x Nx: 0.10 W.D.: 27.8 mm 10x Nx: 0.25 W.D.: 8.0 mm 40x Nx: 0.65 W.D.: 0.6 mm 100x0il Nx: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current Ac 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil JCover-115 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 y ears warranty on parts and one year (1) on service XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX		Focusing: Stage height movement (coarse					
limit stopper, Torque adjustment for coarse adjustment knob, Fine focus knob (minimum adjustment gradations: 2.5µm) Revolving Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 300 inclined binocular tube interpupillary distance adjustment: 370.0 – 432.9mm Objectives: Plan achromat, anti- fungus 4x Nx: 0.10 W.D.: 27.8 mm 10x Nx: 0.25 W.D.: 8.0 mm 40x Nx: 0.65 W.D.: 0.6 mm 100x0il Nx: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current Ac 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil JCover-115 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 y ears warranty on parts and one year (1) on service XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX							
adjustment gradations: 2.5µm) Revolving Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 300 inclined binocular tube interpupillary distance adjustment range: 48 – 75 mm, Evepoint adjustment: 370.0 – 432.9mm Objectives: Plan achromat, anti- fungus 44 NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Fleid Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml (01 Immersion 10ml Oil Immersion 10ml (10 Immersion 10ml Oil Immersion 10ml (10 Immersion 10ml Oil Immersion 10ml (10 PC) WCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) WCP (10 Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X		limit stopper, Torque adjustment for coarse					
Nosepiece: Fixed quadruple nosepiece Stage: Wire movement mechanical fixed stage Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 300 inclined binocular tube interpupillary distance adjustment: 370.0 – 432.9mm Objectives: Plan achromat, anti- fungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) LYCP Power Cord LYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X		adjustment knob, Fine focus knob (minimum					
Wire movement mechanical fixed stage Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 300 inclined binocular tube interpupillary distance adjustment range: 48 – 75 mm, Eyepoint adjustment: 370.0 – 432.9mm Objectives: Plan achromat, anti- fungus 4x Na: 0.10 W.D.: 27.8 mm 10x Na: 0.25 W.D.: 8.0 mm 40x Na: 0.65 W.D.: 0.6 mm 100xOil Na: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 v 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service Xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx		adjustment gradations: 2.5µm) Revolving					
Traveling range: 76 mm (X) x 30 mm (Y), Specimen holder, Specimen position scale Observation Tube: 30o inclined binocular tube interpupillary distance adjustment: 370.0 – 432.9mm Objectives: Plan achromat, anti- fungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.94g Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 W/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X		Nosepiece: Fixed quadruple nosepiece Stage:					
Specimen holder, Specimen position scale Observation Tubes: 300 inclined binocular tube interpupillary distance adjustment range: 48 – 75 mm, Eyepoint adjustment: 370.0 – 432.9mm Objectives: Plan achromat, antifungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 v 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil VCP Power Cord (10 pc) NESS4800 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service XX-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-							
Observation Tube: 300 inclined binocular tube interpupillary distance adjustment range: 48 – 75 mm, Eyepoint adjustment: 370.0 – 432.9mm Objectives: Plan achromat, antifungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 W/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service XX-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-							
interpupillary distance adjustment range: 48 – 75 mm, Eyepoint adjustment: 370.0 – 432.9mm Objectives: Plan achromat, antifungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Flectric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil VCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Urco Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
75 mm, Eyepoint adjustment: 370.0 – 432.9mm Objectives: Plan achromat, antifungus vA NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover-015 wih print (10 pc) UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
432.9mm Objectives: Plan achromat, anti- fungus 4x Na: 0.10 W.D.: 27.8 mm 10x Na: 0.25 W.D.: 8.0 mm 40x Na: 0.65 W.D.: 0.6 mm 100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
fungus 4x NA: 0.10 W.D.: 27.8 mm 10x NA: 0.25 W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100x0il NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service **X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X							
W.D.: 8.0 mm 40x NA: 0.65 W.D.: 0.6 mm 100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml Oil Ust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X*X							
100xOil NA: 1.25 W.D.: 0.13 mm Eyepiece (10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer							
(10x): Field Number (FN): 20 (Anti-fungus) Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X		and the second control of the contro					
Weight Approx. 5.9kg Rated Voltage/Electric Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
Current AC 100-240 V 50/60 Hz 0.4 A Power Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
Consumption: Less than 2 W Microscope frame for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 W/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
for transmitted microscopy with LED illuminator, binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
binocular tube, a pair of eyepiece 10X (F.N.20), quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
quadruple revolving nosepiece, right-handle mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
mechanical stage, abbe condenser and plan objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
objectives (4X, 10X, 40X, 100X), including AC adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
adapter, fixing belt for transportation. (10 unit) Oil Immersion 10ml Oil Immersion 10ml Oil Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
Immersion 10ml (20 bottle) Dust Cover-015 w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
w/print Cover-015 (WP) Dust Cover Type-015 with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X		Oil Immersion 10ml Oil Immersion 10ml Oil					
with print (10 pc) UYCP Power Cord UYCP Power Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X		Immersion 10ml (20 bottle) Dust Cover-015				Village and American	
Cord (10 pc) AF538400 Eyepiece pointer AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
AF538400 Eyepiece pointer (10 pc) Microscope Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
Bag 3 years warranty on parts and one year (1) on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
on service X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X							
X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-X-		1 3 /					
For the official use at the Natural Science Department (Reah Ann Torres)		on service					
Department (Reah Ann Torres)		The transfer provide the real provides the provide the provide the real transfer the provide the real provides the provide					
(Reah Ann Torres)		The state of the comment of the property of the comment of the com					
(Requested by: Tracy N. Tacuban)		(Reah Ann Torres)					
		(Requested by: Tracy N. Tacuban)					
				and the same of th			

3. bacsec.2024 F101



Republic of the Philippines

ILOILO SCIENCE AND TECHNOLOGY UNIVERSITY

La Paz, Iloilo City

Department: Bids and Awards Committee Doc. Code: QF-BAC-02 Rev. No.: 00 Effective Date: July 1, 2022

REQUEST FOR QUOTATION

(PR/JR NO.)		SVP-2024-205	Date	:	AUG 0	7	2024
(11931(110.)	•		Doc Track No.	:	68877		

SCH	EDULE OF REQUIREMENT	
Particular	University	Supplier's Offer
Delivery Period	Requirement	
Delivery Period	15 days after receipt of Purchase Order	
Warranty Period	Standard 30 months Warranty	
After Sales Services (<i>If applicable</i>)	One-year (1) free services	

SUPPLIER'S INFORMATION				
Supplier's Business Name				
Supplier's Business Address				
Contact No.				
Fax No.				
Email Address				
TIN No.				
PhilGEPS Registration No.				

Signature over Printed Name	
Position/Designation	
Date	