Section VII. Technical Specifications

NO.	SPECIFICATION		STATEMENT OF COMPLIANCE				
		[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence Evidence shall be in the form of manufacturer's un-amended sales literature unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder of supplier liable for prosecution.]					
		Procurement of Speaker and othe	r Supplies for	Various Of	fices		
		UNIT QTY BRAND Statement of Compliance					
1	Speaker	Powered speaker 10" *800W Peak 10@ woofer 350 watts 1.35@ Titanium Tweeter 50 watts power 400 Watts continous 800 wAtts Peak Freq Range 40Hz to 20Hz Input Balance XRL with complete line input output connectors with durable stand 15 inch Active Way Powered Speaker Class D Amplifier With speaker bracket for installation	units	4			
2	Audio Mixer	Mixer 12 Channels *Sound mixer 12 channels D-PRE mic preamps deliver clean, transparent, and natural sound 3- band USB 2.0 for recording and playback With computer and tablet SPX effects processors 24 effect Pad pad switch on mono inputs for managing loud sources	units	2			
3	Cable	Microphone Cable *Black Mic Cable 6.7MM (100 meters per Roll) Original, Made in Germany Stereo Type Microphone Wire with ground length 100M roll, Cable thickness approx. 0.7M or 6.77mm Color Black, durable, flexible design eliminates kinks and twists High fidelity transmission, Heavy duty, Low impedence	roll	1			
4	Connector	Audio Connector Male and Female *3 pole female and male XLR cable connector Good quality, metal housing (10pcs each)	sets	10			
5	Connector	Audio Connector PL Mono *1/4" professional phone plug, 2 pole, nickel contacts, nickel shell The heavy duty professional phone	pcs	8			

		plug series improves on the design			
		of the existing C series by offering the thinnest available A-gauge 1/4"			
		plug with unique Neutrik chuck type strain relief ont he market			
		The slimline shell with a width of			
		14.5 mm meets the most recent requirements fo highest density			
		jackfileds (15.88mm jack pitch)		×	
6		*The nickel 3.5mm Right-angle			
	Connector	stereo plusg is a metal bodied	noe	6	
		3.5mm jack plug with chuck type strain relief for secure cable	pcs	0	
		retention It accepts cables from 2.0 to 4.5mm			
7		UHF Wireless Microphone			
		Microphone Echo Level and EQ			
		AUX Input			
		Line Output USB/Micro SD Card Input			
		Battery and AC Powered (Rechargeable)			
	Portable	Charging Time: 3.5 hours			
	Speaker with	Usage Time: 5 to 6 hours (5 hours continued use) (6 hours staggered	lot	1	
	Microphone	use)			
		Voltage: 12 Volts Capacity: 14Ah			
		700W Max Power 605H * 372D * 325W mm			
		Fee 32GB Flash Drive			
		With charger Recording Function			
		Miscro SD Card Storage			
8		Rechargeable Portable Speaker with 2 wireless Microphone-Power			
	Speaker	output-550w	unit	2	
		Frequency Response - 60hz-10Khz, Input Power - AC 220V-240V 50Hz,			
		External DC/12V, with built in Battery speaker unit 12 in bass and			
		with handle, Cable System			
		microphone input Dimension: 15"			
		Delivery Period: 30 days			
		Warranty Period : 1 Year			

