

Section VII. Technical Specifications

ITEM NO.	SPECIFICATION		STATEMENT OF COMPLIANCE			
	Procurement of Tripod Turnstile and Face Recognition Module for Turnstile. <u>PhP 1,024,000.00).</u>		[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]			
	Specification		UNIT	QTY	BRAND	Statement of Compliance
1.	Tripod Turnstile	TCP/IP network communication: The communication data is specially encrypted to relieve the concern of privacy leak Bidirectional (entering/exiting) lane LED indicates the entrance/ecit and passing status except "Pg" type model. With key buttons to configure turnstile's functions and parameters offline. Support ISAPI protocol to integrated with 3rd software management system. MCBF > 3 million times Interface: Lock control 2, Alarm input 2, Alarm output 2, Network interface 1, RS-485 6 (The interfaces can be switched to RS-232 via DIP switch), RS-232 6 interfaces can be switched to RS-232 via DIP switch; 2 for fingerprint module or QR code scanner, Card Capacity: 60,000 Event Capacity: 180,000 Power supply method : 100 to 240 VAC Throughput: More than 35 persons per minute	unit	8		

		Throughput: More than 35 persons per minute Card type: EM;M1, compatible with Hikcentral Professional V 2.6.1.20240816				
2	Face recognition module for turnstile	Built-in IO output or Wiegand output to communicate with the third-party turnstile 7 inch LCD touch screen, 2 Mp camera max 50,000 faces, and max 100,000 events distance: 0.3M to 3M, duration 0.2s/user accuracy 99%, TCP/IP, Wi-Fi communication remote live view via RTSP protocol, IP65 To be integrated with the unit above. compatible with Hikcentral Professional V 2.6.1.20240816	unit	8		
		Supplier must have an ISO Certificate of Brand Manufacturer and Certificate of Platinum Dealer Partner Supplier must have a Manufacturers Certificate (indicating project name and end user) Supplier must have a local store/office (within the locality) for fast after sales service				
		Warranty Period: 2 YEARS After Sales Services: Local service within the locality				
		Delivery Period: 45 Calendar days Upon Receipt of the NTP				