

# Section VII. Technical Specifications

ITEM NO.	SPECIFICATION		STATEMENT OF COMPLIANCE			
	<b>Procurement of Photocopier</b> <b>- PhP 1,375,000.00</b>		[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]			
	Specification		UNIT	QTY	BRAND	Statement of Compliance
	Photocopier- (President, PDAS, CIT- MIT/DIT, VPEA, Admin)	1. General Requirements Type: Digital Color Laser Multifunction Copier Functions: Print, Copy, Scan Technology: Laser Control Panel: Minimum 7" Color Touchscreen Display Warm-Up Time: 25 seconds or less First Copy Out Time: Approx. 7.5 sec (B/W), 10.5 sec (Color)  2. Printing and Copying Print/Copy Speed (A4/Letter): Minimum 20 ppm (color & mono) Resolution (Print): Minimum 1200 x 600 dpi Multi-Copy Function: 1 to 999 copies Monthly Duty Cycle: Minimum 50,000 pages  3. Paper Handling Paper Size Support: maximum A3 (including custom sizes) Standard Paper Input: 2 x 500-sheet trays + 100-sheet bypass tray Paper Weight Support: 52 – 256 gsm Duplexing: Automatic two-sided copy/print (Standard) Document Feeder: Auto Reverse Document Feeder  4. Scanning Scan Speed: Minimum 55 ipm simplex Resolution (Scan): Up to 600 dpi  5. Connectivity & Compatibility Network Interface: Gigabit Ethernet USB: Minimum 1 x USB Host Port	unit	5		

		6. Memory and Storage RAM: At least 2 GB  7. Energy Efficiency Certification: ENERGY STAR or equivalent  8. Physical and Other Requirements Stand: Floor-standing unit or with optional cabinet/metal stand Toner Types: CMYK Toner Yield (Approx): CMY: 9,000 pages, K: 15,000 pages  9. Inclusions One full set of starter toner (CMYK) One full set of reserve toner (CMYK) AVR 2KVA User manual, driver software				
1						
		<b>Warranty Period: 1 year (parts) and lifetime (service)</b> <b>For Equipment:</b> <b>Aftersales Services: With local service center within locality</b>				
		<b>Delivery Period: 30 Calendar days Upon Receipt of the NTP</b>				